

# **MICHELIN® X® TWEEL® SSL**

**AIRLESS RADIAL TIRE**



## **DESIGNED FOR USE ON SKID STEER LOADERS**

The MICHELIN® X® TWEEL® SSL AT (All Terrain) airless radial tire is ideal for use on a broad range of surfaces. The Hard Surface (HS) and Hard Surface Traction (HST) models help provide maximum tread life on pavement.

- ✓ No Maintenance
- ✓ No Compromise
- ✓ No Downtime

[michelintweel.com](http://michelintweel.com)



# MICHELIN® X® TWEEL® SSL

## AIRLESS RADIAL TIRE

### NO MAINTENANCE

MICHELIN® X® TWEEL® SSL is one single unit, replacing the current tire/wheel/valve assembly. There is no need for complex wheel/tire mounting equipment. Once they are bolted on, there is no air pressure to maintain.

### NO COMPROMISE

Productivity can be increased because the MICHELIN X TWEEL SSL provides outstanding stability and enables a skid steer to work rapidly with more comfort for the operator, reducing driver fatigue while improving productivity. The MICHELIN X TWEEL SSL delivers a consistent footprint with strong wear life that is two to three times that of the pneumatic tire at equal tread depth. Additionally, the unique energy transfer within the poly-resin spokes reduces the "bounce" associated with pneumatic tires.

### NO DOWNTIME

MICHELIN X TWEEL SSL performs like a pneumatic tire, but without the risk and costly downtime associated with penetrations and impact damage.

Deep open tread designed for excellent cleaning and traction. A deep layer of undertread means the core can be retreaded again and again.

Zero degree belts and CompositCoil™ proprietary design provide great lateral stiffness, while resisting damage and absorbing impacts.



Universal, 8 hole, heavy gauge steel hub will easily bolt onto all standard skid steer machines.

Michelin's proprietary Comp10 Cable™ forms a semi-rigid "shear beam", and allows the load to hang from the top.

High strength, poly-resin spokes carry the load and absorb impacts, help dampen the ride, and provide a unique energy transfer that reduces pneumatic bounce.



MSPN	Description	Max Load @ 15km/h	Section Width	Overall Diameter	Rolling Circum.	Static Loaded Radius	Contact Area	Tread Depth	Undertread	Weight
34735	12N16.5 X TWEEL SSL All Terrain	4,400 lbs.	12.1 in	33.1 in	94.7 in	15.8 in	61.4 in <sup>2</sup>	31/32nds	12/32nds	226.0 lbs
31483	12N16.5 X TWEEL SSL Hard Surface	4,400 lbs.	12.1 in	33.9 in	94.7 in	16.1 in	53.1 in <sup>2</sup>	50/32nds	6/32nds	260.0 lbs
64828	12N16.5 X TWEEL SSL Hard Surface Traction	4,400 lbs.	12.1 in	33.9 in	94.7 in	16.1 in	53.1 in <sup>2</sup>	48/32nds	8/32nds	255.0 lbs
37131	10N16.5 X TWEEL SSL All Terrain	3,700 lbs.	10.1 in	30.2 in	86.8 in	14.1 in	55 in <sup>2</sup>	31/32nds	10/32nds	177.0 lbs

NOTE: Product measurements are subject to change and are listed here for your convenience. Please see your MICHELIN representative for up-to-date data.

#### USA

Michelin North America, Inc.  
One Parkway South  
Greenville, SC 29615  
1-888-622-2306

#### Canada

Michelin North America (Canada), Inc.  
2500 Daniel Johnson, Suite 500  
Laval, Quebec H7T 2P6  
1-888-871-4444

#### Mexico

Industrias Michelin, S.A. de C.V.  
Av. 5 de febrero No. 2113-A  
Fracc. Industrial Benito Juarez  
7 6120, Querétaro, Qro. Mexico  
011 52 442 296 1600

[michelintweel.com](http://michelintweel.com)

